



CHIPSEALER CT

FORWARD APPLICATION

CONVEYOR BELT HOPPER

CUSTOMIZABLE



ERGONOMICS

- All information available on a unique in-cab monitor
- An ergonomic working position developed with the users
- Options designed to simplify your jobsites



SAFETY

- Forward application
- Conveyor belts tipper (hooking risks eliminated)
- Operator working from the cab



CUSTOMISATION

- More than 50 options : GREENSWIFT, ADR, milk of lime slurry, night heating, loading arm, twist-lock removability...
- Many combinations to suit your needs on your jobsites



RELIABILITY

- Your CHIPSEALER CT project is developed, designed and produced in our factory in Cossé le Vivien 53 France
- The equipment is tested on our approved test bench
- Test bench report provided on delivery



VERSATILITY

- Use as a sprayer, chip spreader or combined
- Full width application or patching
- Potholes treatment



EFFICIENCY

- CEM compliant dosing
- In-cab joystick allows the operator to work precisely
- For patching, the DUOSPRAY option guarantees an optimal dosage on all the application width

New ergonomic cab: SMART CAB

A complete control workstation with 3 tools for your jobsites.

The Joystick, simple and ergonomic to use, allows the selection of nozzles and/or gates, the selection to spray emulsion and/or chips, the spraybar adjustment, the individual right and left spraybar height controls.

The ergonomic armrest with secondary controls has been designed for greater ease of use and allows: control of additional gates for binder/chip application, short-cuts for changing the binder/chip dosage, control of gates with/without binder/chip.

12" colour touch screen on a swivel support to access the different functions.

The following informations are always available on the screen :

- Binder/chips dosage
- Spraying width
- Binder pump speed
- Truck speed
- Warning messages in case of peripheral component failure
- Integrated rear view cameras

TECHNICAL SPECIFICATIONS



MORE VIDEOS OF
OUR PRODUCTS
ON OUR YOUTUBE
CHANNEL

Type of binder	Bitumen emulsion, hot bitumen (modified or not), ADR option possible
Tank capacity	From 4,000 L to 9,000 L (increment of 1,000 L)
Insulation	100 mm rock wool covered by aluminium or stainless steel casing
Type of heating	Direct or indirect (with thermal oil)
Spraybar	4.4 m telescopic
Binder application rate	From 0.1 to 3 kg/m ²
Hand lance	15 m with winder
Chip size	From 2 mm to 14 mm
Tipper capacity	From 6 to 8 m ³
Chipsreader	3,2 m (without auger) 3,6 m 4,4 m
Chips application rate	2 to 16 L/m ²
Control	In cabin : joystick with 12" screen / computerized application rates



SECMAIR - Rue Auguste et Louis Lumière - 53230 Cossé-Le-Vivien
Tel. +33 (0)2 43 98 27 76 - Fax +33(0)2 43 98 86 49
info@secmair.fayat.com - secmair.fayat.com

